

STANDARD FEATURES AND SPECIFICATIONS Rocky Mountain...14'/24'/28' Homes

EXTERIOR

Colour coordinated metal fascia

Vinyl siding & white vinyl soffit

4/12 pitch roof with non-residential eaves (3 sides)

and 16" eave on HE (14' wide)

4/12 pitch hinged roof with 12" eaves HE & rear,

16" on long walls (24' and 28' wide)

2 Exterior GFI receptacles

Exterior FF tap - kitchen sink

30-year architectural fiberglass shingles

7/16" roof sheathing

Perimeter ventilation

Separate receptacle for heat tape

2x8 floor joists 16" o.c.

3/8" wall sheathing on inside & outside of exterior walls

Insulation: R22 walls; R40 ceiling; R32 floor

2" x 6" side walls @ 24" o.c. - 8' walls

12" tubular steel frames with detachable hitch

19/32" T&G subfloor

8' ceiling height

Engineered roof trusses to 2.8 KPA snow load

EXTERIOR DOORS

Insulated steel exterior doors, 36" front and rear (where possible) with peepholes and deadbolts

Lever door handles

Coach lights at all exterior doors

WINDOWS

1.4 U Value, dual Low E argon filled

PVC windows and sills with screens

Blue skin windows

KITCHEN

Adjustable shelves in all cabinets - (2) upper & (1) lower

Double stainless-steel sink

Roller door slides on all drawers

Microwave cabinet with separate circuit (most models)

PVC cabinet doors

18 cu. ft. frost free refrigerator

30" electric range with clock and timer

2-speed range hood with light and fan vented to exterior

White kitchen appliances

Single lever faucet with vegetable sprayer

Crown moulding on cabs

Communication box (empty) at kitchen area

Upper corner cab - narrow reed glass

ALL HOMES ARE BUILT TO MEET OR EXCEED

CSA Z240 SPECIFICATIONS FOR B.C.

HOME IS BUILT TO MEET ENERGY ZONE 5

ALL PRICES ARE F.O.B. LETHBRIDGE, AB

ALL PRICES DO NOT INCLUDE GST

ALL PRICES DO NOT INCLUDE ASSOCIATION FEES

STANDARDS IN EFFECT AS OF 2/14/25

UTILITY ROOM

Plumbed and wired for washer/dryer

High-efficiency gas furnace with electronic ignition

Dryer vent rough in

50 GAL. Electric hot water tank

Overhead solid shelf at washer/dryer area

Insulated lines in HWT cavity

BATHROOMS

Exhaust fan with humidistat in main bath

Exhaust fan in ensuite on separate switch

Towel bar and towel ring (most models) in each bath

Cosmetic box in main bath

Showerhead and shower rod in all baths

GFI receptacle in all baths

Walled tub/shower with single lever pressure balanced

faucet in both baths

Single lever faucets in all baths

Theatrical lights in all baths

Dual flush toilets

INTERIOR

2x4 interior walls

Textured ceiling throughout

Decorative vinyl covered drywall

6 mil. vapour barrier includes switches and receptacles

Plush carpet in LR, MBR (Hall & FR where applicable on sectionals)

Quality vinyl floor covering

Cathedral LR, DR, Kitchen (14')

Cathedral throughout (24' & 28')

Ceiling lights in all bedrooms

Wire for ceiling light in living room

Pendant light in dining room

Solid shelving in all closets

White embossed interior doors with lever handles

4" ceramic tile backsplash at kitchen & vanities with tile edging

Vinyl wrap moulding throughout

MISCELLANEOUS

Electric smoke/CO detector(s)

100-amp service panel

Electrical conduit through floor

White receptacles and switches

LED Light bulb package

Shut off valves, hammer arrestors, vacuum breakers, solar ready

Pig tail, electrical

Programmable thermostat

Airtight Protocol

26* Room

This is not a fully detailed specification. SRI Homes - Regent reserves the right to change specifications, designs, materials and suppliers without notice and without incurring obligation. Information

contained herein is from data available at the time of printing